




Description

The Hongo is an AISI 430 stainless steel transitional profile with a thickness of 0.8 mm / 0.031", designed to hide cuts and damages to the coating.



Profile

			h: 10 mm / 3/8" 10 mm / 3/8" 10 mm / 3/8"	w: 16 mm / 5/8" 22 mm / 7/8" 40 mm / 1 37/64"	Length: 2.50 m / 98"
-----------------------------------------------------------------------------------	-----------------------------------------------------------------------------------	-----------------------------------------------------------------------------------	-----------------------------------------------------------	---------------------------------------------------------------	--------------------------------

Check availability of other sizes in your country.

Uses and applications

It is applied after the installation of two adjacent coatings at the same height. The design with vertical partition enables anchoring with the adhesive to be used.

Uses: interior.



Advantages

- The joint-covering hongo is very resistant to corrosion and to highly-abrasive products.
- It is enduring and it does not rust.

Material properties

430 stainless steel guarantees durability, functional performance and high quality.

It offers a soft and tactile finish that requires low maintenance and easy cleaning.

Simple resistance to wear and heat, it must be applied in areas with slightly corrosive conditions, environments that require a lower level of mechanical resistance and moderate temperatures.

Composición: 17% chrome and 0.12% carbon.

Installation method

1. Choose the suitable width of the profile according to the gap between both floors to be joined.
2. Fill the joints with adhesive and fit in the profile pressing downward.



Cleaning and maintenance

It is imperative to clean the material immediately after its installation to avoid cement/forge remnants or iron particles from scrubbers or tools that may cause pitting corrosion.

Pay special attention to areas that are hard to reach and make sure to remove all dust and other debris. For applications in interior areas, you can use water with dishwashing liquid, detergent or liquid soap to remove dirt and possible fingerprints that may have been left behind. In high-polish finishes, you can use a glass/crystal cleaner. When cleaning stainless steel, always make sure to rinse it properly and dry it completely to prevent fogging.

It is not advisable to use:

- Steel wool since it could scratch the surface.
- Hydrochloric acid or iron products in prolonged contact.
- Materials that contain chlorides.
- Setting accelerators that contain chlorides.
- Regular steel cleaners.

How to install the hongo 
www.youtube.com/atrimglobal