

Description

Curved-design profile, made of 6063 T5 aluminum alloy and textured finish, that delicately integrates the joint of ceramic tiles and porcelain tiles protecting their edges.



Profile

Size: 12 mm x 12 mm x 2.50 m / 1/2" x 1/2" x 98"

Material: Painted aluminum

	<p>h: 12 mm / 1/2"</p> <p>w: 12 mm / 1/2"</p>	<p>Length: 2.50 m / 98"</p>
--	---	--

Uses and applications

Its 12-mm / 0.047" curved design enables the joint of two coatings at a 90° angle and it is a straight finish solution for walls, exterior corners, counters and columns.

Uses: Interior walls.



Advantages

- It decorates the joint between two planes and protects the edge of ceramic tiles and porcelain tiles avoiding damages and scratches.
- Very low polish level.

Material properties

- The combination between the textures and the different shades of paint provides a textured and tactile surface.
- It presents a thicker matte appearance, compared to the standard dust coating.
- The thicker coating offers a more even color in the whole surface of the material.

Instructions for use

- 1.** Choose the profile according to the sizes of the coating to be covered.
- 2.** Apply adhesive with a notched trowel on the surface.
- 3.** Complete the installation of the coating and place the Bullnose Edge Guard.
- 4.** Press the profile on the floor until the adhesive sticks out of the punched "A".
- 5.** Place the adjacent porcelain tile adjusting it at the same level as the edge guard.
- 6.** Level the coating with crosshead spacers to guarantee an even joint.
- 7.** Fill the joint with grout or forge.
- 8.** Clean the profile with a damp cloth to prevent the glue from drying on the surface.



Cleaning and maintenance

Clean the aluminum profiles with a soft cloth regularly. The surface must be protected from objects than may scratch it. When using a neutral cleaner, it must be diluted with cold water and then dried to remove the damp effect. If damp persists, clean it with a 5% solution of detergent or neutral soap in water and wipe with a cloth that does not contain particles to avoid scratching.

It is not advisable to use:

- Steel wool.
- Abrasive or remover products, such as strong acids (hydrochloric and perchloric).
- Strong bases (caustic soda or ammonia).
- Carbonated solutions.
- Citric acid.
- Waxes, petroleum jelly, lanolin or similar products.
- Haloalkane solvents (hydrofluoroethers or chlorinated solvents).
- Setting accelerators that contain chlorides.

For more information about measurements and colors, go to
www.atrimglobal.com



How to install quadra edge guard for walls
www.youtube.com/watch?v=atrimglobal



Argentina
0810-22-ATRIM (28746)
ventasatrim@atrimglobal.com

Chile
+56 2 3210 3817
ventas@atrimglobal.com

Colombia
+57 601 508 4846
ventas@atrimglobal.com

Mercosur
+54 11 2821 8900
ventas@atrimglobal.com

Centroamérica / Caribe
+57 316 4405239
ventas@atrimglobal.com